



#### DATA SHEET

## 3Com® SuperStack® 3 Switch 4900 and SuperStack 3 Switch 4900 SX

### Key Benefits

High-performance,  
affordable, copper  
and fiber Gigabit  
switching

#### Performance

Wirespeed, non-blocking Gigabit Ethernet switching across all ports delivers maximum performance for heavily utilized networks.

#### Affordability

The 3Com® SuperStack® 3 Switch 4900 family of fixed configuration managed switches provides unmatched value, industry leading performance without compromise.

#### High Availability

Robust availability features include link aggregation, support for Rapid Spanning Tree, Redundant Power Supply system, and e-mail or pager status notification, ensuring maximum uptime for critical applications.

#### Prioritize Business Critical Traffic

Advanced Class of Service support including support for four queues per port, 802.1p, and multilayer packet classification capabilities to allow prioritization of critical traffic.

The 3Com SuperStack 3 Switch 4900 delivers high performance, feature-rich Gigabit Ethernet switching in a simple, affordable platform, making it an excellent solution for small-to-medium-size networks with growing bandwidth requirements. It's also perfect for large enterprises that require low cost yet high functionality Gigabit Ethernet switching across their data center and the server farm or wiring closet.

#### Layer 3 Switching

Support for wire-speed Layer 3 switching capabilities enhances performance, provide network control and security, and enable logical segmentation of networks based on VLANs.

#### Flexibility

Modular architecture lets you support different Gigabit media in the same workgroup platform, enabling placement of the SuperStack 3 Switch 4900 anywhere in the network, regardless of cabling type.

#### Powerful Management

3Com Network Supervisor application is included with discovery, mapping, monitoring, and alerting for easy network administration. Intuitive interface speeds network-wide set-up of switch traffic prioritization.

#### Lifetime Limited Warranty

Ensures peace of mind. Lifetime warranty includes fans and power supplies.

The twelve-port switch is available in two configurations, to support multi-mode fiber optic cabling or traditional Category 5 cabling. Mix and match both fiber and copper Gigabit media leveraging optional Gigabit switching modules for cost-effective performance in a simple, integrated platform.

## Specifications

### Connectors

3C17700: 12 auto-negotiating 100BASE-TX/ 1000BASE-T ports configured as Auto-MDIX (cross-over).

3C17702: 12 1000BASE-SX ports using MT-RJ connectors.

3C17710: Switch 4900 series expansion module supporting 4 1000BASE-SX ports using MT-RJ connectors

3C17711: Switch 4900 series expansion module supporting 4 x 1000BASE-T ports using RJ-45 connectors configured as Auto-MDIX

3C17712: Switch 4900 series expansion module supporting 4 x 1000BASE-LX ports using MT-RJ connectors

3C17714: Switch 4900 series expansion module supporting 4 x GBIC ports

### Dimensions

Height: 6.6 cm (2.6 in)  
Width: 44 cm (17.3 in)  
Depth: 37 cm (14.5 in)  
Weight: 6.5 kg (13 lb)

### Performance

23 million packets per second

### Reliability

MTBF @ 40°C: 326,000 hours

### Environmental Requirements

Operating temperature: 0° to 40°C (32° to 104°F)

Storage Temperature: -40° to +70°C (-40° to +158°F)

Operating Humidity: 10% to 90% relative humidity non-condensing

Standards: EN60068 (IEC68)

### Safety Agency Certifications

UL1950, EN60950, CSA22.2 No. 950, IEC 60950

### Emissions

EN55022 Class A, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, AS/NZS 3548 Class A, CNS 13438 Class A

Immunity: EN55024

Heat Dissipation: 50 W maximum (168 BTU/hr maximum)

### Power Supply

AC Line Frequency 50/60 Hz

Input Voltage Options 90-240 VAC

Current Rating 4.5A maximum

### Switching

#### Features/Functionality

802.1D

802.1Q VLAN Support

IGMP Snooping

Link Aggregation

### SNMP Standards

SNMP Protocol (RFC 1157)

MIB-II (RFC 1213)

Bridge MIB (RFC 1493)

RMON MIB II (RFC2021)

Remote Monitoring MIB (RFC 1757)

Interface MIB (2233)

MAU MIB (RFC 2668)

### Administration

UDP (RFC 768)

IP (RFC 791)

ICMP (RFC 792)

TCP (RFC 793)

ARP (RFC 826)

TFTP (RFC 783)

TELNET (RFC854)

BOOTP/DHCP (RFC1542)

HTTP (RFC2068)

### Routing Protocols

RFC 1058 RIP

RFC 1519 CIDR

RFC 1723 RIP v2

RFC 2131 BootP/DHCP Relay

### Warranty and Non-Warranty Services

Limited Lifetime Warranty, for as long as the original Customer owns the product, or five years after product discontinuance, whichever occurs first. Includes fan and power supply.

After registering the product online, other free support services such as telephone support, fast hardware replacement, and software updates may also be available, depending on regional availability and retailer participation.

### Management

3Com Network Supervisor provided free of charge on accompanying CD

Web interface

Command line interface management

SNMP compatibility

## Ordering Information

3Com SuperStack 3 Switch 4900	3C17700
-------------------------------	---------

3Com SuperStack 3 Switch 4900 SX	3C17702
----------------------------------	---------

### Optional Modules and Accessories

3Com SuperStack 3 Switch 4900 1000BASE-SX Module	3C17710
--	---------

3Com SuperStack 3 Switch 4900 1000BASE-T Module	3C17711
---	---------

3Com SuperStack 3 Switch 4900 4-port 1000BASE-LX module	3C17712
---	---------

3Com SuperStack 3 Switch 4900 4-Port GBIC Module	3C17714
--	---------

3Com 1000BASE-SX GBIC	3CGBIC91
-----------------------	----------

3Com 1000BASE-LX GBIC	3CGBIC92
-----------------------	----------

3Com 1000BASE-LH70 GBIC (up to 70km)	3CGBIC97
--------------------------------------	----------

3Com SuperStack Advanced Redundant Power System Chassis	3C16071B
---	----------

3Com SuperStack Advanced Redundant Power System Type 3 325W	3C16075
---	---------



3Com Corporation, Corporate Headquarters, 5400 Bayfront Plaza, P.O. Box 58145, Santa Clara, CA 95052-8145.

To learn more about 3Com solutions, visit [www.3com.com](http://www.3com.com). 3Com Corporation is publicly traded on Nasdaq under the symbol COMS.

Copyright © 2002 3Com Corporation. All rights reserved. 3Com and SuperStack are registered trademarks of 3Com Corporation. The 3Com logo is a trademark of 3Com Corporation. All other company and product names may be trademarks of their respective companies. While every effort is made to ensure the given information is accurate, 3Com does not accept liability for any errors or mistakes which may arise. All specifications are subject to change without notice. 400632-006 04/02